

SHK kontaktor

230/400
V AC

35x7.5

Ta
-5...+60 °C

Uimp
4 kV

ON-OFF-ON...
sc/h
x360

x3.000.000

x100.000

Ui
500 V


V0
UL94

IP
20


TRACON	Um	In (A)	NC NO	W (mm)	[mm ²]	
SHK2-25	230 V AC	25 A	2 x NO	18 mm	1-6 mm ²	klasični
SHK2-25V11	230 V AC	25 A	1 x NO + 1 x NC	18 mm	1-6 mm ²	klasični
SHK2-25-24	24 V AC	25 A	2 x NO	18 mm	1-6 mm ²	klasični
SHK2-40	230 V AC	40 A	2 x NO	36 mm	2,5-25 mm ²	klasični
SHK2-40V11	230 V AC	40 A	1 x NO + 1 x NC	36 mm	2,5-25 mm ²	klasični
SHK2-63	230 V AC	63 A	2 x NO	36 mm	2,5-25 mm ²	klasični
SHK2-63V11	230 V AC	63 A	1 x NO + 1 x NC	36 mm	2,5-25 mm ²	klasični
SHK3-25	230 V AC	25 A	3 x NO	36 mm	1-6 mm ²	klasični
SHK3-40	230 V AC	40 A	3 x NO	54 mm	2,5-25 mm ²	klasični
SHK3-63	230 V AC	63 A	3 x NO	54 mm	2,5-25 mm ²	klasični
SHK4-25	230 V AC	25 A	4 x NO	36 mm	1-6 mm ²	klasični
SHK4-25V22	230 V AC	25 A	2 x NO + 2 x NC	36 mm	1-6 mm ²	klasični
SHK4-40	230 V AC	40 A	4 x NO	54 mm	2,5-25 mm ²	klasični
SHK4-40V22	230 V AC	40 A	2 x NO + 2 x NC	36mm	2,5-25 mm ²	klasični
SHK4-63	230 V AC	63 A	4 x NO	54 mm	2,5-25 mm ²	klasični
SHK4-63V22	230 V AC	63 A	2 x NO + 2 x NC	54 mm	2,5-25 mm ²	klasični




1NO+1NC




2 NO




2NO+2NC



3 NO



4 NO



TRACON
ELECTRIC®

Tel: +386 - (0)2 - 600-16-07 • tracon.lendava@tracon.si; www.si.traconelectric.com

Več informacij lahko dobite pri komercialistu. Telefonske številke so objavljene spletni strani pod INFO .. KONTAKT

SHK kontaktor

230/400
V AC

35x7.5

Ta
-5...+60 °C

U_{imp}
4 kV

ON-OFF-ON...
sc/h
x360



x3.000.000

x100.000

U_i
500 V


V0
UL94

IP
20


TRACON	U _m	I _n (A)	NC NO	W (mm)	[mm ²]		
SHK2-25K	230 V AC	25 A	2 x NO	18 mm	1-6 mm ²		z ročico
SHK2-40K	230 V AC	40 A	2 x NO	36 mm	2,5-25 mm ²		z ročico
SHK2-63K	230 V AC	63 A	2 x NO	36 mm	2,5-25 mm ²		z ročico
SHK4-25K	230 V AC	25 A	4 x NO	36 mm	1-6 mm ²		z ročico
SHK4-40K	230 V AC	40 A	4 x NO	36 mm	2,5-25 mm ²		z ročico
SHK4-63K	230 V AC	63 A	4 x NO	54 mm	2,5-25 mm ²		z ročico





2 NO




4 NO



TRACON	U _m	I _n (A)	NC NO	W (mm)	[mm ²]		
SHK-S11	230 V AC	5 A	1 x NO + 1 x NC	9 mm	1-6 mm ²		stranski
SHK-S20	230 V AC	5 A	2 x NO	9 mm	1-6 mm ²		stranski



1NO+1NC



2 NO

